






































MOY MATERIALS Fastener Range

Product code	Product sample	Application	Headform	Installation tools	Tool illustrations
R75 X L		Insulation sleeve for use in combination with BS-4,8, BS-S-4,8, TI-T25-6,3, TIA-T25-6,3 TI-S-Z10-6,3 or TS-T25-6,0 fasteners.	N/A	ZA1/4-M6-300 drive shank + fastener bit ZH-11-RING ZA1/4-DL Depth locator	
R48 X L		Membrane sleeve for use in combination with BS-4,8, BS-S-4,8, TI-T25-6,3, TI-S-Z10-6,3 or TS-T25-6,0 fasteners.	N/A	ZA1/4-M6-300 drive shank + fastener bit ZH-11-RING ZA1/4-DL Depth locator	
R45 X L		Membrane sleeve for use in combination with BS-4,8, BS-S-4,8, TI-T25-6,3, TIA-T25-6,3 TI-S-Z10-6,3 or TS-T25-6,0 fasteners.	N/A	ZA1/4-M6-300 drive shank + fastener bit ZH-11-RING ZA1/4-DL Depth locator	
FI-R-20 X L		Sleeve for use with the BSA-P-70x70 or the isoweld FI-P-16,0-PVC or FI-P-16,0-TPO stress plates. Compatible fasteners are the BS-4,8, BS-S-4,8 BS-6,1, TI-T25-6,3, TIA-T25-6,3, TI-S-Z10-6,3, or TS-T25-6,0.		ZA1/4-M6-300 drive shank + fastener bit ZH-12-RING ZA1/4-DL Depth locator	

SH-18/65 X 85mm	 <p>Alternatives</p>	Termination bar sleeve for use in combination with BS-4,8, BS-S-4,8, TI-T25-6,3 TI-S-Z10-6,3 or TS-T25-6,0 fasteners.	N/A	ZA1/4-M6-300 drive shank + fastener bit	
MNA-6,0 X L		Nail Plugs for fixing termination bar into masonry.	PZ	Z2-25-HEX1/4 6,0 mm drill + Hammer	
BS-4,8 X L		Carbon steel self drilling fastener for use with R75, R50, FI-R-20 or SH18/65x85 sleeves into Steel / Plywood / OSB3 decks.	Torx T25	ZA1/4-M6-300 drive shank + fastener bit ZA1/4-DL Depth locator	
BS-S-4,8 X L		A4, 316 stainless steel self drilling fastener for use with R75, R50, FI-R-20 or SH18/65x85 sleeves into Steel / Plywood / OSB decks.	Torx T25	TS-T25-M6 bit	
TI-T25-6,3 X L		Carbon steel fastener for use with R75, R50, FI-R-20 or SH18/65x85 sleeves. Also ID-70x70 or IRD-82x40 stress plates into concrete decks.	Torx T25	ZA1/4-M6-300 drive shank ZA1/4-DL Depth locator TS-T25-M6 bit	
TI-S-Z10 X L		A2, 304 Stainless Steel fastener for use with R75, R50, FI-R-20 or SH18/65x85 sleeves. Also ID-70x70 or IRD-82x40 stress plates into concrete decks.	SQ3	SQ3-40-M6 bit SDS / ZVK drill bits	
TIA-T25-6,3 X L		Adjustable carbon Steel fastener for membrane and insulation attachment to concrete roof decks. Compatible with the R75, R50 & FI-R-20 sleeves Ideal for tapered insulation on concrete decks and for precast / hollowcast concrete beams.	Torx T25	ZA1/4-M6-300 drive shank ZA1/4-DL Depth locator T25-32-M6 bit AJ-M6 Adjusting tool ZVK-STOP drill	

<p>TS-T25-6,0 X L</p>		<p>Carbon steel fastener for use with the R75, R50, FI-R-20 or SH18/65x85 sleeves for fixing into plywood & OSB3 decks.</p>	<p>Torx T25</p>	<p>ZA1/4-M6-300 drive shank ZA1/4-DL Depth locator TS-T25-M6 bit</p>	
<p>TPR-6,3 X L</p>		<p>Aluminium rivets for use with decks not suitable for screw fixings.</p> <p>Compatible with the ID-70x70, IRD-82x40 and IF/IG-C-82x40mm stress plates.</p>	<p>n/a</p>	<p>IP50-B Battery tool HSS-7,0 X L / L or SDS-7,0 X L / L drills</p>	
<p>IF-70X70 IR-82X40</p>		<p>Stress plates for combination with BS-4,8 & BS-S-4,8 fasteners.</p> <p>IF-70x70mm for insulation attachment.</p> <p>IR-82x40mm for membrane attachment.</p>	<p>n/a</p>		<p>See Appropriate fastener details above</p>
<p>BSA-P-70x70</p>		<p>Stress plates for combination with the FI-R-20 sleeves.</p> <p>For compatible fasteners see the FI-R-20 sleeve description above.</p>	<p>n/a</p>		<p>See Appropriate fastener details above</p>
<p>ID-70X70 IRD-82X40 IF/IG-C-82x40</p>		<p>Stress plates for combination with TI-T25-6,3 , TS-T25-6,0 & TPR-L-6,3 fasteners.</p> <p>ID-70x70mm for insulation attachment.</p> <p>IRD-82x40mm for membrane attachment.</p> <p>IF/IG-C-82x40mm for membrane attachment for hard surfaces.</p>	<p>N/A</p>		<p>See Appropriate fastener details above</p>

<p>IWF-5,2 X L</p> <p>IWS-5,0 X L</p> <p>IRC/W-82X40</p>		<p>Countersunk timber fasteners for attachment of membrane or termination bar direct to plywood or OSB3 deck.</p> <p>Membrane stress plate for hard surfaces.</p> <p>IWF-5,2 X L carbon steel fastener.</p> <p>IWS-5,0 X L A2, grade 304 stainless steel.</p>	<p>PH2</p> <p>PZ</p>	<p>ZA1/4 universal bit holder</p> <p>H2-25-HEX1/4 bit</p> <p>Z2-25-HEX1/4 bit</p>	
<p>MW-40-F</p> <p>MW-50-F</p>		<p>Membrane stress plates for hard surfaces.</p> <p>MW-40-F for use with IW-F-5,2 or BS-4,8 fasteners on ply or OSB3 decks</p> <p>MW-50-F for use with TI-T25-6,3 on concrete decks.</p>	<p>N/A</p>		<p>See Appropriate fastener details above</p>
<p>FI-P-16,0-PVC</p> <p>FI-P-16,0-TPO</p>		<p><i>isoweld</i> Induction welding plates for combination with FI-R-20 sleeves for fixing PVC & TPO membrane.</p> <p>Install the plates using the tooling for the FI-R-20 sleeves and install the membrane using the <i>isoweld</i> 3000 tooling.</p> <p>FI-P-16,0-PVC is pink in colour.</p> <p>FI-P-16,0-TPO is green in colour.</p>	<p>n/a</p>	<p><i>isoweld</i> 3000</p>	
<p>FI-P-6,8-PVC</p> <p>FI-P-6,8-TPO</p>		<p><i>isoweld</i> Induction welding plates for full metallic connection to the deck for fixing PVC and TPO Membrane.</p> <p>For use in combination with BS-6,1, BS-S-4,8, TS-T25-6,1, TI-T25-6,3, TI-S-Z10-6,3, IWF-5,2, IW-S-5,0 & TPR-L-6,3 fasteners.</p>	<p>n/a</p>		