

Technical Data Sheet

Enke Glass Primer

Product Description:

Solvent-based primer for Enkopur on glass and ceramic substrates.

Properties:

Rapidly drying adhesion promoter for glass/tiles, even in areas where water collects for extended periods of time.

Designated Use:

Primarily for connections to glazing or ceramic tiling but also for the waterproofing of tile flooring, under loosely laid slabs or similar.

Certification:



Application:

Apply with a roller, a paint brush or a thoroughly saturated cloth.

Technical data:

Delivery form:	Liquid
Colour:	Colourless
Flash-off time:	30-60 minutes (depending on weather)
Viscosity:	Approx. 2 mPa·s at 20°C
Density:	Approx. 0.8 g/cm ³
Flash point:	Approx. 12°C

Consumption:

Approx. 50 g (approx. 60 ml)/m².

Delivery form:

1 l disposable tin packing drum.

Storage:

Cool, in sealed original containers, protected from sunlight; for more information see Safety Data Sheet.

Shelf life:

At least 12 months if stored properly.

Disposal:

As soon as you have finished using the product, empty the packing drums completely to allow proper disposal, ensuring they are scraped out and drip-free. Tin containers emptied of residue can be recycled using appropriate steel recycling channels. As a certified user of the German recycling logo Enke can provide a list of collection points. The user shall dispose of non-hardened adhesive materials or larger amounts of product residues in tin containers at his costs as this is special waste.

MOY Materials Ltd has taken care to ensure that the information provided in the literature is correct and up to date. However, it is not intended to form any part of a contract or provide a guarantee. Purchasers/intending purchasers should contact MOY Technical to check whether there have been any changes to the information since publication of the literature. Please ensure you have read the hazard labels and material safety data sheet before using this product.

