

Technical Data Sheet

Enke Polyflex Fleece

Product Description:

Thermally fixed, needled polyester fleece featuring good flexibility and tear resistance in longitudinal and transverse directions. Enke Polyflex fleece has good mechanical properties and is ideally suited to being saturated with any of the Enke coatings. The special texture of this type of fleece allows true-to-contour waterproofing of even extremely uneven substrates.

Enke Polyflex fleece serves as a crack-bridging reinforcement for Enke roof coatings to enable reliable waterproofing of flat roofs, balconies, terraces or exterior corridors.

Prefabricated shaped fleece parts also allow fast, secure and easy application in detailing and connection areas.

Certification:



Technical data:

Basis:	Needled polyester fleece (White)
Surface weight:	110 g/m ²
Thickness:	Approx 0.8mm
Longitudinal tensile strength:	> 25 daN/10cm
Transverse tensile strength:	> 26 daN/10 cm
Storage life:	Virtually unlimited

Consumption:

1.1 m/m² (with an overlap of approx. 10 cm)

Delivery form:

Internal / External corners:	Box of 20 pieces
Collars 75 mm, 100 mm or 150 mm dia.:	Box of 10 pieces

Rolls with a length of 50m and a width of 100mm, 150mm, 200mm, 300mm, 500mm or 1,000m

Storage:

Cool, dry location; for more information see Safety Data Sheet.

Shelf life:

At least 12 months if stored properly.

MOY Materials Ltd has taken care to ensure that the information provided in the literature is correct and up to date. However, it is not intended to form any part of a contract or provide a guarantee. Purchasers/intending purchasers should contact MOY Technical to check whether there have been any changes to the information since publication of the literature. Please ensure you have read the hazard labels and material safety data sheet before using this product.

