

## Declaration of Performance Paratherm F™ Tapered

Paratherm F™ Tapered  
CPR.2013.MOY.PthermF\_T.007

Unique identification code of the product-type:  
Intended use/es:  
Manufacturer:

Paratherm F™ Tapered  
Thermal insulation for buildings  
Moy Materials Ltd. Unit K, South City Business Park,  
Whitestown Way, Tallaght, Ireland.  
System 4 (Reaction to Fire), System 3 (Other properties)  
BS-EN 13165:2012+A2:2016  
FIW München:0751

System/s of AVCP:  
Harmonised technical specification:  
Notified body/ies:

Essential characteristics		Performance
Thermal resistance	Thermal resistance $R_D$ ((m <sup>2</sup> .K)/W)	NPD
	Thermal conductivity $\lambda_D$ (W/(m.K))	0,022
	Thickness tolerance	T2
Reaction to fire	Reaction to fire	F
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability of the reaction to fire of the product as placed on the market	NPD
	Durability of thermal resistance and thermal conductivity against ageing/ degradation	NPD
Durability of Thermal Resistance against heat, weathering, ageing / degradation	Thermal resistance $R_D$ ((m <sup>2</sup> .K)/W)	NPD
	Thermal conductivity $\lambda_D$ (W/(m.K))	0,022
	Durability characteristics	NPD
	Dimensional stability under specified temperature and humidity condition	DS(70,90)3 DS(-20,-)1
	Deformation under specified compressive load and temperature conditions	DLT(2)5
Determination of the aged values of thermal resistance and thermal conductivity	$\lambda_D$ 0,022 W/m·K	



## Declaration of Performance Paratherm F™ Tapered

Compressive strength	Compressive stress or compressive strength	CS(10\Y)150
Tensile / Flexural strength	Tensile strength perpendicular to faces	TR40
Durability of compressive strength against ageing / degradation	Compressive creep	NPD
Water permeability	Short term water absorption	NPD
	Long term water absorption	NPD
	Flatness after one sided wetting	NPD
Water vapour permeability	Water vapour transmission	NPD
Acoustic absorption index	Sound absorption	NPD
Continuous Glowing combustion	Glowing Combustion	NPD
Release of dangerous substances to the indoor environment	Release of dangerous substances	NPD
NPD: No Performance Determined		

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

.....  
**Brian Conroy**  
 Group Technical Director  
 Moy Materials Ltd  
 Date signed: 31/10/2023  
 Issue Number: v007