ROOF ACCESSORIES

Declaration of Performance GreenGuard® GG300



GreenGuard® GG300

CPR.2013.MOY.GreenGuard GG300.008

Unique identification code of the product-type:

Intended use/es:

Manufacturer:

System/s of AVCP:

Harmonised technical specification:

Notified body/ies:

GreenGuard® GG300

Thermal insulation for buildings

Moy Materials Ltd. Columbia Mills, 14/15 Sir John Rogerson's Quay,

Dublin 2, D02 E409, Ireland.

System 4 (Reaction to Fire), System 3 (Other properties)

BS-EN 13165:2012+A1:2015

FIW München:0751

Essential characteristics		Performance	
		d _N 30mm	0.85
Thermal resistance	Thermal resistance R _p ((m².K)/W)	d _N 40mm	1.15
		d _N 50mm	1.45
		d _N 60mm	1.75
		d _N 70mm	2.05
		d _N 80mm	2.35
		d _N 100mm	2.90
		d _N 120mm	3.50
		d _N 140mm	4.10
		d _N 150mm	4.40
		d _N 180mm	4.55
		d _N 30-180	0.033
	Thermal conductivity λ_D (W/(m.K))	u _N 30 100	0.033
	Thickness tolerance	d _N <50	T1 ±2mm
		d _N 50-120	T1 -2 3mm
		d _N >120	T1 -2 +6mm
Reaction to fire	Reaction to fire	F	-
- IIII 6			
Durability of reaction to fire against heat, weathering, ageing / degradation	Durability characteristics	NPD	
weathering, ageing / degradation			
Durability of thermal resistance against heat, weathering, ageing/degradation	Dimensional stability under specified	DS(70,90)	
	temperature and humidity conditions	,	
	Deformation under specified compressive	NPD	
	load and temperature conditions		
Compressive strength	Compressive stress or compressive strength	CS(10/Y)300	
Compressive strength			
Tensile / Flexural strength	Tensile strength perpendicular to faces	TR100	
Durability of compressive strength against ageing		NPD	
/ degradation	Compressive creep		
Water permeability	Long term water absorption by total		
	immersion	NPD	
		_	
	Long term water absorption by diffusion	NPD	
	Freeze-thaw resistance after long term	NPD	
	water absorption by diffusion		
Water vapour permeability	Water vapour transmission	NPD	
Closed cell content	Closed cell content	NPD	
Continuous Glowing combustion	Glowing Combustion	NPD	
	Glowing Combustion		
Release of dangerous substances to the indoor	Release of dangerous substances	NPD	
environment	neiease of daligerous substances		

ROOF ACCESSORIES

Declaration of Performance GreenGuard® GG300



accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Brian Conroy

Group Technical Director

Moy Materials Ltd

Date signed: 15/10/2024 Issue Number: v008

MS TEAMS\MOYTechnical\DOP-CE-UKCA\Insulation\GreenGuard GG300 DoP [CE] 15.10.24 v008