


Declaration of Performance PARAFLEX NT4

Accompanying Technical Documentation	Declaration of Performance n° 0N4008-00	
		13 22

1. Unique identification code of the product type: **0N4008**
2. Product Identification:

PARAFLEX NT4		
Length, Width: 8x1 (-1%) m	Thickness: 4,00 mm	Reinforcement: Stabilised polyester
Finishing TOP/BOTTOM: TERMOTENE / TERMOTENE	Installation (*): Mechanical Fixing and Torch	

(*): Storage in vertical position, out of sun and freezing. Stabilise for 24 h at +5°C, prior to use, where otherwise TDS

3. Intended uses:

Harmonised technical spec. EN - BS EN	Intended uses	
13707:2004+A2:2009	<input type="checkbox"/> <input type="checkbox"/> <input checked="" type="checkbox"/> <input checked="" type="checkbox"/> <input type="checkbox"/>	FLEXIBLE SHEET FOR WATERPROOFING – DEFINITIONS AND CHARACTERISTICS REINFORCED BITUMEN SHEET FOR ROOF WATERPROOFING (*): - SINGLE LAYER - EXPOSED MULTILAYER – TOP LAYER - EXPOSED MULTILAYER – UNDERLAY OR INTERMEDIATE LAYER - UNDER HEAVY PROTECTION - ANTIROOT (*): Refer to our technical assistance service about correct stratigraphy
13859-1:2010	<input type="checkbox"/>	FLEXIBLE SHEETS FOR WATERPROOFING – DEFINITIONS AND CHARACTERISTICS: - UNDERLAY FOR DISCONTINUOUS ROOFING
13969:2009	<input checked="" type="checkbox"/>	FLEXIBLE SHEETS FOR WATERPROOFING - DEFINITIONS AND CHARACTERISTICS: - BITUMEN DAMP PROOF SHEETS INCLUDING TANKING SHEET
13970:2004/A1:2006	<input type="checkbox"/>	FLEXIBLE SHEETS FOR WATERPROOFING - DEFINITIONS AND CHARACTERISTICS: - BITUMEN WATER VAPOUR CONTROL LAYERS
14695:2010+AC:2011	<input type="checkbox"/>	FLEXIBLE SHEETS FOR WATERPROOFING - DEFINITIONS AND CHARACTERISTICS: REINFORCED BITUMEN SHEET - WATERPROOFING OF CONCRETE BRIDGE DECKS

4. Name of manufacturer: IMPER ITALIA srl, Via Rita Atria 9, 10079 Mappano (TO), Italy
5. Authorised Representative: Moy Materials Ltd, Columbia Mills, 14/15 Sir John Rogerson's Quay, Dublin 2, D02 E409.
6. Systems of assessment and verification of constancy of performance of the construction product :

Harmonised technical spec. EN – BS EN	Systems of assessment and verification of constancy of performance of the product
13707:2004+A2:2009, 13969:2004, 14695:2010+AC:2011	AVCP 2+
13859-1:2010, 13970:2004/A1:2006	AVCP 3

7. In accordance with the above-mentioned AVCP systems, notified bodies/laboratories have performed the initial inspection of the manufacturing plant of factory production control, or the initial type testing provided, and the continuous surveillance, assessment and evaluation of factory production control, and issued the certificate of conformity of the factory production control, or the test reports as described below:

BITUMEN

Harmonised technical spec. EN – BS EN	Notified body	Code	Certificate of conformity/ Test report
13707:2004+A2:2009	BUREAU VERITAS ITALIA	1370	1370 – CPR 0054
13859-1:2010	---	---	---
13969:2004	BUREAU VERITAS ITALIA	1370	1370 – CPR 0054
13970:2004/A1:2006	---	---	---
14695:2010+AC:2011	---	---	---

8. Declared performance:

Essential characteristics	U.M.	Tolerances	Performances	Harmonised technical spec. EN – BS EN
External fire performance ⁽¹⁾	Class	-	NPD	EN 13707:2004+A2:2009
Reaction to fire	Class	-	E	EN 13707:2004+A2:2009, EN 13969:2004, EN 13859-1:2010, EN 13970:2004/A1:2006
Watertightness	kPa	≥	60	EN 13707:2004+A2:2009, EN 13969:2004, EN 13859-1:2010, EN 13970:2004/A1:2006, EN 14695:2010+AC:2011
Tensile properties L/T	N/50 mm	± 20%	800/600	EN 13707:2004+A2:2009, EN 13969:2004, EN 13859-1:2010, EN 13970:2004/A1:2006, EN 14695:2010+AC:2011
Elongation L/T	%	± 15% abs	50/50	EN 13707:2004+A2:2009, EN 13969:2004, EN 13859-1:2010, EN 13970:2004/A1:2006, EN 14695:2010+AC:2011
Root resistance	-	-	NPD	EN 13707:2004+A2:2009
Resistance to static loading	kg	≥	25	EN 13707:2004+A2:2009, EN 13969:2004
Resistance to impact	mm	≥	1250	EN 13707:2004+A2:2009, EN 13969:2004 EN 13970:2004/A1:2006
Tear resistance L/T	N	± 30%	160/180	EN 13707:2004+A2:2009, EN 13969:2004, EN 13859-1:2010, EN 13970:2004/A1:2006
Joint resistance: - Peel joint	N/5 cm	± 20N	NPD	EN 13707:2004+A2:2009, EN 13969:2004
- Joint strength	N/5 cm	± 20%	OJB	EN 13707:2004+A2:2009, EN 13969:2004 EN 13970:2004/A1:2006
Cold flexibility	°C	≤	- 25	EN 13707:2004+A2:2009, EN 13969:2004, EN 13859-1:2010, EN 13970:2004/A1:2006
Water vapour properties	μ	≥	20,000	EN 13970:2004/A1:2006
Durability:				
- Cold flexibility	°C	+15	-10	EN 13707:2004+A2:2009
- Flow resistance at elevated temperature	°C	-10	≥100	EN 13707:2004+A2:2009, EN 14695:2010+AC:2011
- UV resistance				EN 13707:2004+A2:2009, EN 14695:2010+AC:2011
- Tensile properties: maximum tensile force L/T	-	-	NPD	EN 13859-1:2010
- Tensile properties: elongation L/T	N/5 cm	±20%	700/500	EN 13859-1:2010
- Watertightness	%	±15 abs	45/45	EN 13859-1:2010
- Water vapour properties	kPa	≥	60	EN 13969:2004, 13859-1:2010, 13970:2004/A1:2006
- Chemical resistance	μ	≥	NPD	EN 13969:2004, 13970:2004/A1:2006
	-	-	NPD	EN 13969:2004, 13970:2004/A1:2006
Res. to dynamic water pressure	kPa	>=	NPD	EN 14695:2010+AC:2011
Watertightness	%	<=	NPD	EN 14695:2010+AC:2011
Bond strength	N/mmq	>=	NPD	EN 14695:2010+AC:2011
Capacity to bridge cracks	°C	<=	NPD	EN 14695:2010+AC:2011
Compatibility	%	>=	NPD	EN 14695:2010+AC:2011
Resistance to heat impact	-	-	NPD	EN 14695:2010+AC:2011
Resistance to compaction	-	-	NPD	EN 14695:2010+AC:2011
Resistance to shear	N/mmq	>=	NPD	EN 14695:2010+AC:2011
Dangerous substance	Not contain dangerous substances in compliance with national standard			

(1) Determination of external fire performance is a system test which can be influenced by system components, thus performance for each individual product cannot be given.

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 8. The declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Mappano,

Legal representative:
Maurizio Alongi

IMPER ITALIA SRL
Via Rita Atria, 9 - 10079
Mappano (TO) - Italy
IT 03764530014